



→ Designed for Indian conditions : Specially designed Polypropylene container, corners reinforced with ribs, ensures the battery is strong enough to withstand bumps and vibrations

→ Reduced effect of vibration : Compact element design ensures battery can withstand high vibration in application

→ Instant start every time : Good cranking power and better life expectancy ensure customer satisfaction

→ Technology : Optimized Alloy System to suit high temperature and low maintenance application

→ Easy handling & spill proof : Special Omega type cover design fitted with Venturi type chamber cover & Anti-splash guard feature - excellent spill resistance characteristic

→ Ready to use : Batteries are factory charged and ready to use condition



18 Month Warranty *
(FOC)
* T&C Apply

Technical Specifications of Exide Gold Range of Batteries

Battery Nomenclature	Ref C20 Capacity (Ah)	Maximum Overall Dimensions (MM)			Nominal Filled Weight (KG)	Electrolyte Volume (LITRES)	Charging Current (A)	CCA at - 18°C As Per			Acid Level Indicator	Battery Layout
		L	W	H				EN	IEC	SAE		
FEG0-GOLD32R	32	197	129	227	9.5	2.5	2.5	-	220	272	Not Present	Right Layout -□□□□+
FEG0-GOLD35R	35	197	129	227	10.5	2.2	3	-	270	332	Not Present	Right Layout -□□□□+
FEG0-GOLD35L	35	197	129	227	10.5	2.2	3	-	270	332	Not Present	Left Layout +□□□□-
FEG0-GOLD65R	65	260	173	225	18.2	4.4	5	-	400	490	Not Present	Right Layout -□□□□+
FEG0-GOLD65L	65	260	173	225	18.2	4.4	5	-	400	490	Not Present	Left Layout +□□□□-
FEG0-GOLD80R	80	305	173	225	23	4.9	6.5	-	420	530	Not Present	Right Layout -□□□□+
FEG0-GOLD88L	88	410	176	235	26.3	7	7	-	430	550	Not Present	Left Layout +□□□□-
FEG0-GOLD100L	100	410	176	235	27.5	6.45	8	-	475	580	Not Present	Left Layout +□□□□-
GEG0-GOLD130R	130	505	182	257	34.5	8.5	9	-	540	700	Not Present	Right Layout -□□□□+
FEG0-GOLD150R	150	508	222	257	41.5	10.9	10.5	-	640	785	Not Present	Right Layout -□□□□+
FEG0-GOLD180R	180	521	278	270	53.8	16	13	-	830	1050	Not Present	Right Layout -□□□□+
FEG0-GOLD100R	100	410	176	234	27.5	6.45	8	-	475	580	Not Present	Right Layout -□□□□+
FEG0-GOLD80L	80	305	173	225	23	4.9	6.5	-	420	530	Not Present	Left Layout +□□□□-
FEG0-GOLD88R	88	410	176	234	26.3	7	7	-	430	550	Not Present	Right Layout -□□□□+